LeanDrum CF (Cold Forming)

- Lavado, enjuague y secado en un pequeño paquete.
- Limpieza por aspersion e inmersión completa.
- Tambor, tanques y cubiertas de acero inoxidable.
- Fácil acceso al tambor
- Bajo costo de mantenimiento.
- Envoltura del tambor perforado.
- Larga vida de la solución.
- Garantía 3-2-1
- Diseñada para aplicaciones de formado en frío; excelente para la mayoría de productos a granel torneados o estampados.

LeanDrum CF

Todas las especificaciones están sujetas a cambio sin previo aviso

CLEANING TECHNOLOGIES GROUP

RANSOHOFF BLACKSTONE-NEY ULTRASONICS CTG ASIA

MODEL NUMBER	LD-CF	
PART PRODUCTION	12 CU FT/Hour @ 2RPM design drum speed vs Drive 1 - 3 RPM	
WASH CAPACITY	100 Gallons (380 Liters)	
RINSE CAPACITY	70 Gallons (266 Liters)	
BLOWER CAPACITY	470 CFM @ 3" SP	
DRUM DIAMETER	18" (457mm)	
LOAD HEIGHT	34" (864mm)	
UNLOAD HEIGHT	30" (762mm)	
FLOOR SPACE (L x W x H)	9' 7" x 4' 7" x 5' 0" (2920 mm X 1400mm X 1525mm)	
UTILITY REQUIREMENTS	460V 3 Ph, 60 Hz	

Ransohoff
(800) 248-9274
4933 Provident Drive
Cincinnati, OH 45246
www.ctgclean.com

Blackstone-NEY Ultrasonics
(800) 766-6606
P.O. Box 220
9 N. Main St.
Jamestown, NY 14702-0220

CTG Asia
(86)0512-66161698
56 Songshan Road
Suzhou New District
Jiangsu Province, China PRC: 215151